




## MINIFIX®

### DESCRIPTION

The MINIFIX® mount comprises an elastomer pad with an anti-slip ridged surface and a threaded stud allowing accurate height adjustment of equipment. Made in two hardnesses (50 and 80 Sh) the MINIFIX® mount is perfectly suited to a variety of applications and is delivered complete with fixing nuts and washers. MINIFIX® mounting nuts and screws are made of steel or stainless steel.

### CHARACTERISTICS



Référence Inox	Référence Acier	Dureté Elastomère	Couleur	Ø A (mm)	B (mm)	C (mm)	D	Plage d'utilisation (daN)
-	530801	50 SBR 80 Nitrile	gris noir	32	15	38	M8 tige	5 - 30 15 - 70
-	530802*	50 SBR 80 Nitrile	gris noir	46	15	-	M10 écrou	10 - 80 25 - 200
530806	530805	50 SBR 80 Nitrile	gris noir	46	15	38	M10 tige	10 - 40 25 - 100
-	530807	50 SBR 80 Nitrile	gris noir	70	25,5	55,5	M12 tige	50 - 180 100 - 350

\* Threaded centre hole.  
See current price list for availability of items.

### APPLICATIONS

Simple and economic, MINIFIX® mountings are particularly suitable for the installation of equipment such as :

- Electrical or electronic enclosures.
- Packaging equipment.
- Test and measuring equipment.
- Equipment for the food industry.
- Laboratory equipment.
- Household appliances.